

SLIMBOX A

Platine • Client léger ATRUST OS

Processor INTEL J1900

Mémoire 4GB • SSD 32 GB

1 HDMI • VGA

2 ports ethernet GbE

2 RS232 ports • 4 USB

Wifi / Bluetooth en option

ATRUST OS communications RDP / CITRIX / VMWARE



Atrust



0~50°C

Système

Chipset	INTEL
Processeur	INTEL J1900
Stockage	MSATA 32GB
Modularité	1 M.2
Mémoire	4GB
Ethernet	2 GbE
Entrées / Sorties	1 VGA
	1 HDMI
	4 USB
	2 RS232 (RS232/422/485)
Alimentation	2 RJ45
	AC 100~240V, 50Hz/60 Hz
	DC 9V~36V

Communication

Ethernet	2 GbE
Wifi (Option)	Wifi AC
Bluetooth (Option)	BT5

Environnement

Temp. fonctionn.	-0°C~50°C
Temp. stockage	0°C ~60°C
Humidité	10%~95%
Vibration	MIL-STD-810H 516.8 procedure I - functional shock, Operating 20G, 11ms (Follow IEC 60068-2-27 half sine)
Certification	FCC/ CE

Dimensions / Construction

Matériau	Acier / Aluminium
Dimensions	200 x 137 x 40 mm
Poids	Environ 2 Kg
Fixation	Equerres de fixations

Protocoles / Gestion

Protocoles	Remote desktop
	Citrix ICA / VMWARE VIEW
	SSH
Management	ATRUST Device manager (ADM)

